

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/039400

International filing date: 23 November 2004 (23.11.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 10/721,526
Filing date: 25 November 2003 (25.11.2003)

Date of receipt at the International Bureau: 05 January 2005 (05.01.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

December 22, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: *10/721,526*

FILING DATE: *November 25, 2003*

RELATED PCT APPLICATION NUMBER: *PCT/US04/39400*

Certified by



Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

22930 U.S. PTO
10/721526
112503

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	SHP026.4.1
First Inventor	SMITH, Daniel K.
Title	Resettable Safety Shield for Medical Needles
Express Mail Label No.	EV068780548US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Mail Stop Patent Application
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

- ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
- ☒ Applicant claims small entity status.
See 37 CFR 1.27.
- ☒ Specification [Total Pages 33]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 42]
- Oath or Declaration [Total Sheets 4]
 - ☒ Newly executed (original or copy)
 - ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 18 completed)
 - ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) name in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
- ☐ Application Data Sheet. See 37 CFR 1.76

- ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - ☐ Computer Readable Form (CRF)
 - Specification Sequence Listing on:
 - ☐ CD-ROM or CD-R (2 copies); or
 - ☐ Paper
 - ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

- ☒ Assignment Papers (cover sheet & document(s))
- ☐ 37 CFR 3.73(b) Statement of Attorney (when there is an assignee) ☒ Power of Attorney
- ☐ English Translation Document (if applicable)
- ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
- ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
- ☐ Nonpublication Request under 35 U.S.C. 122 (b)(2)(B)(i). Applicant must attach form PTO/SB/35 or its equivalent.
- ☒ Other: Check No. 10098 for \$628.00

18. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in the first sentence of the specification following the title, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) of prior application No.: 10/409,819

Prior application information:

Examiner

Art Unit:

For CONTINUATION OF DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

19. CORRESPONDENCE ADDRESS

☒ Customer Number: 26,152 OR ☐ Correspondence address below

Name

Address

City

State

Zip Code

Country

Telephone

Fax

Name (Print/Type) Paul S. Evans

Registration No. (Attorney/Agent)

36,130

Signature

Date

11/25/2003

This collection of information is required by 37 CFR 1.53(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL
for FY 2004

Effective 10/01/2003. Patent fees are subject to annual revision.

☒ Applicant claims small entity status. See 37 CFR 1.27TOTAL AMOUNT OF PAYMENT (\$)**628.00****Complete if Known**

Application Number	
Filing Date	November 25, 2003
First Named Inventor	Daniel K. SMITH
Examiner Name	
Art Unit	
Attorney Docket No.	SHP026.4.1

METHOD OF PAYMENT (check all that apply)☒ Check ☐ Credit card ☐ Money Order ☐ Other ☐ None☒ Deposit Account: 19-3542Deposit
Account
Number
Deposit
Account
NameSpecialized Health
Products, Inc.

The Director is authorized to: (check all that apply)

☐ Charge fee(s) indicated below ☒ Credit any overpayments☒ Charge any additional fee(s) or any underpayment of fee(s)☐ Charge fee(s) indicated below, except for the filing fee to the above-identified deposit account.**FEE CALCULATION****1. BASIC FILING FEE**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
1001 770	2001 385	Utility filing fee	385
1002 340	2002 170	Design filing fee	
1003 530	2003 265	Plant filing fee	
1004 770	2004 385	Reissue filing fee	
1005 160	2005 80	Provisional filing fee	
SUBTOTAL (1) (\$)			385

2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE

Total Claims	Extra Claims	Fee from below	Fee Paid
33	-20** = 13	9	117
Independent Claims	5	-3** = 2	43
Multiple Dependent			86

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
1202 18	2202 9	Claims in excess of 20
1201 86	2201 43	Independent claims in excess of 3
1203 290	2203 145	Multiple dependent claim, if not paid
1204 86	2204 43	** Reissue independent claims over original patent
1205 18	2205 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$)**203**

**or number previously paid, if greater. For Reissues, see above

FEE CALCULATION (continued)**3. ADDITIONAL FEES**

Large Entity Small Entity


Fee Code (\$)	Fee Code (\$)	Fee Description	Fee Paid
1051 130	2051 65	Surcharge - late filing fee or oath	
1052 50	2052 25	Surcharge - late provisional filing fee or cover sheet	
1053 130	1053 130	Non-English specification	
1812 2,520	1812 2,520	For filing a request for ex parte reexamination	
1804 920*	1804 920*	Requesting publication of SIR prior to Examiner action	
1805 1,840*	1805 1,840*	Requesting publication of SIR after Examiner action	
1251 110	2251 55	Extension for reply within first month	
1252 420	2252 210	Extension for reply within second month	
1253 950	2253 475	Extension for reply within third month	
1254 1,480	2254 740	Extension for reply within fourth month	
1255 2,010	2255 1,005	Extension for reply within fifth month	
1401 330	2401 165	Notice of Appeal	
1402 330	2402 165	Filing a brief in support of an appeal	
1403 290	2403 145	Request for oral hearing	
1451 1,510	1451 1,510	Petition to institute a public use proceeding	
1452 110	2452 55	Petition to revive - unavoidable	
1453 1,330	2453 665	Petition to revive - unintentional	
1501 1,330	2501 665	Utility issue fee (or reissue)	
1502 480	2502 240	Design issue fee	
1503 640	2503 320	Plant issue fee	
1460 130	1460 130	Petitions to the Commissioner	
1807 50	1807 50	Processing fee under 37 CFR 1.17(q)	
1806 180	1806 180	Submission of Information Disclosure Stmt	
8021 40	8021 40	Recording each patent assignment per property (times number of properties)	40
1809 770	2809 385	Filing a submission after final rejection (37 CFR 1.129(a))	
1810 770	2810 385	For each additional invention to be examined (37 CFR 1.129(b))	
1801 770	2801 385	Request for Continued Examination (RCE)	
1802 900	1802 900	Request for expedited examination of a design application	

Other fee (specify)

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$)**40****SUBMITTED BY**

(Complete if applicable)

Name (Print/Type)	Paul S. Evans	Registration No. (Attorney/Agent)	36,130	Telephone	801-298-3360
Signature		Date	11/25/03		

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This collection of information is required by 37 CFR 1.17 and 1.27. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Express Mail No. EV068870548US

PATENT APPLICATION
Docket No: SHP026.4.1

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that the enclosed complete patent application consisting of 33 pages of specification, 42 sheets of drawings, and Check No. 10098 for \$628.00 in the matter of the Patent Application of Specialized Health Products, Inc. for RESETTABLE SAFETY SHIELD FOR MEDICAL NEEDLES, a Combined Declaration and Power of Attorney, as well as an Assignment with form PTO-1595, is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated below in an envelope addressed to MS Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.


JODI BARRUS

EV068780548US
EXPRESS MAIL LABEL NUMBER

EV068780548US

November 25, 2003
DATE OF DEPOSIT

RESETTABLE SAFETY SHIELD FOR MEDICAL NEEDLES

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This patent application is a continuation-in-part of U.S. Utility Patent Application Serial No. 10/409,819, filed in the U.S. Patent and Trademark Office on April 8, 2003 by Ferguson et al., which is a continuation-in-part of U.S. Utility Application Serial No. 10/322,288, filed in the U.S. Patent and Trademark Office on December 17, 2002 by Ferguson et al., which claims priority to U.S. Provisional Patent application Serial No. 60/424,655, filed in the U.S. Patent and Trademark Office on November 7, 2002 by Bagley et al., and U.S. Utility Patent Application Serial No. 10/202,201, filed in the U.S. Patent and Trademark Office on July 23, 2002 by Ferguson et al., which is a continuation-in-part of U.S. Utility Patent Application Serial No. 09/809,357, filed in the U.S. Patent and Trademark Office on March 15, 2001 by Ferguson et al., the entire contents of each of these disclosures being hereby incorporated by reference herein.

BACKGROUND**1. Technical Field**

The present disclosure generally relates to safety shields for medical needles, and more particularly, to resettable safety shields that protect a needle point of a medical needle.

2. Description of the Related Art

Problems associated with inadvertent needle sticks are well known in the art of blood sampling, percutaneous medication injection and other medical procedures involving use of medical needles. Significant attention has been focused on needle stick problems due to the contemporary sensitivity of exposure to AIDS, Hepatitis and other serious blood-borne pathogen exposures.

Procedures for removing a needle from a patient commonly require a technician to use one hand to place pressure at the wound site where the needle is being withdrawn, while removing the needle device with the other hand. It is also common practice for an attending technician to give higher priority to care for the patient than is given to disposal of a needle. In the case of typical needle devices without safety shields, such priority either requires the convenience of an available sharps container within reach or another means for safe disposal without leaving the patient's side. Providing adequate care while following safety procedures is often compounded by the patient's physical condition and mental state, such as in burn units and psychiatric wards. Under such conditions, it is difficult to properly dispose of a used needle while caring for a patient.

The widespread knowledge and history associated with needle care and disposal problems have resulted in numerous devices for preventing accidental needle sticks. Problems of current safety devices include difficulty of use and high cost due to their complexity and number of parts.

Other known devices employ sheaths that are spring activated, telescoping, pivoting, etc. These devices, however, may disadvantageously misfire or be cumbersome to activate. Further drawbacks of current devices include high manufacturing cost due to complexity and the number of parts. Thus, these type prior art devices may not adequately and reliably shield medical needle apparatus to prevent hazardous exposure.

Consequently, there remains a need to provide a more satisfactory solution for needle safety devices by overcoming the disadvantages and drawbacks of the prior art. Therefore, it would be desirable to provide a more adequate and reliable medical needle shield apparatus that employs a safety shield slidably movable along a medical needle to prevent hazardous exposure to a needle tip. It would be advantageous to provide such a safety shield that is capable of being reset to safely allow re-use of certain needle apparatus. Such a needle shield apparatus should be easily and reliably movable to shield a needle tip of a needle cannula.

SUMMARY

Accordingly, the present disclosure addresses a need for a medical needle shield apparatus which effectively and inexpensively protects a tip of a medical needle after use. The present disclosure resolves related disadvantages and drawbacks experienced in the art. More specifically, the apparatus and method of this invention constitute an important advance in the art of safety needle devices.

In one particular embodiment, a medical needle shield apparatus is provided in accordance with the principles of the present disclosure. The medical needle shield apparatus includes a needle hub having an outer needle cannula extending therefrom to a distal end. An inner needle is disposed for slidable movement with the outer needle cannula. At least one shield is extensible from a retracted position to an extended position to enclose a distal end of the inner needle. The shield includes a binding member disposed within the shield and defines binding surfaces that form an aperture configured for slidable receipt of the inner needle between the retracted position and the extended position.

The binding member includes at least one drag inducing member such that the member engages the inner needle during slidable receipt of the inner needle to create a drag force with the inner needle. The drag force facilitates rotation of the binding member relative to a longitudinal axis of the inner needle such that the binding surfaces engage the inner needle to prevent slidable movement of the inner needle in the extended position of the shield. The binding member further includes a needle communicating surface extending therefrom such that the needle communicating surface is engageable with the inner needle to prevent rotation of the binding member. A retainer extends transversely from the binding member for releasable engagement with the needle hub.

The binding member may be rotatable, relative to a longitudinal axis of the inner needle, between a non-binding orientation whereby the inner needle is slidable relative to the binding member and a binding orientation whereby the binding surfaces engage the inner needle to prevent slidable movement of the inner needle in the extended position of the at least one shield. The binding member may include one or more outwardly arcuate arms that extend to the needle-communicating surface.

The inner needle can be attached to a handle for manipulation thereof. The needle hub may define a hub slot configured for receipt of the retainer. The needle hub may be releasably mountable with a housing of the at least one shield. The medical needle shield apparatus may further include a plurality of shields.

5 The at least one drag inducing member may define a cavity that is substantially aligned with the aperture. The cavity is configured for slidable receipt of the needle to create the drag force with the needle. The binding member may include a substantially planar aperture plate that includes the binding surfaces that form the aperture. The at least one drag inducing member may include a pair of arms extending from the aperture
10 plate. The arms can have curled end portions spaced apart from the aperture plate. The arms can include deflectable members.

 The shield can include a housing that defines at least one blocking member extending from an interior surface thereof. The at least one blocking member can be engageable with the binding member for urging the binding member to a binding
15 orientation. The aperture plate is axially movable for engagement with the at least one blocking member that causes rotation of the binding member to a binding orientation.

 A binding member reset surface extends transversely from the binding member. The needle hub includes a hub reset surface aligned to contact with the binding member reset surface of an activated binding member when the shield housing is brought to mate
20 concentrically with the needle hub. The hub reset surface deflects the binding member reset surface along with the needle engagement surface to a position above the inner needle surface and urges the binding member from the binding orientation to the sliding orientation. Concurrently, due to contact between the hub reset surface and binding member reset surface, the hub retainer is urged into a position that reengages the needle
25 hub and retains the needle hub to the needle shield. In an illustrative embodiment, the hub reset surface is the distal facing surface of the hub retainer.

 The medical needle shield apparatus may further be supported for relative rotational movement by at least one bearing.

In an alternate embodiment, the medical needle shield apparatus includes a shield being extensible from a retracted position to an extended position to enclose a distal end of the outer needle cannula. The shield defines a probe guide at a distal end thereof that is configured for receipt of a probe. The probe is configured for slidable movement with
5 the outer needle cannula.

In another embodiment, the medical needle shield apparatus includes a needle hub having an outer needle cannula extending therefrom to a distal end. An inner needle is disposed for slidable movement with the outer needle cannula. A handle is attached to the inner needle and defines a flash chamber in communication with the inner needle.
10 The flash chamber has a fitting, such as a luer connection, that facilitates connection to a medical device. A shield is releasably mountable to the needle hub and extensible from a retracted position to an extended position to enclose a distal end of the inner needle. The handle is disposed adjacent the shield.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The foregoing and other features and advantages of the present invention will be more fully understood from the following detailed description of the exemplary embodiments, taken in conjunction with the accompanying drawings in which:

FIGURE 1 is a perspective view of one particular embodiment of a medical needle shield apparatus in accordance with the principles of the present disclosure;

20 FIGURE 2 is a perspective view of the embodiment shown in FIGURE 1 in a shielded configuration;

FIGURE 3 is a cutaway perspective view of a shield of the medical needle shield apparatus shown in FIGURE 1 in a non-binding orientation;

FIGURE 4 illustrates the cutaway perspective view of the medical needle shield
25 apparatus shown in FIGURE 2 in a binding orientation;

FIGURE 5 is a perspective view of the housing of a needle safety apparatus as shown in FIGURE 1;

FIGURE 6 is a cutaway perspective of the grip element of a needle safety apparatus as shown in FIGURE 1;

FIGURE 7 is an enlarged perspective view of a binding member of the medical needle shield apparatus shown in FIGURE 1;

5 FIGURE 8 is a perspective view of the needle shield apparatus as shown in FIGURE 1 having a protective needle sheath installed thereon;

FIGURE 9 is an alternate enlarged perspective view of the binding member shown in FIGURE 7;

10 FIGURES 10 – 11 are cutaway perspective views of the medical needle safety apparatus showing engagement between hub reset surface and binding member reset surface according to the present disclosure;

FIGURE 12 is a cutaway perspective view of an embodiment of the medical needle safety apparatus according to the present disclosure adapted for use with a luer lock needle hub;

15 FIGURE 13 is a cutaway perspective view the medical needle safety apparatus as shown in FIG 12 in a shielded configuration;

FIGURE 14 is an enlarged perspective view of the medical needle safety apparatus as shown in FIGURE 12 showing engagement between hub reset surface and binding member reset surface according to the present disclosure;

20 FIGURE 15 is an enlarged perspective view of the medical needle safety apparatus as shown in FIGURE 12 in a reset configuration;

FIGURE 16 is a perspective view of an embodiment of a medical needle shield apparatus adapted for use with a bone biopsy needle in accordance with the principles of the present disclosure;

25 FIGURE 17 is an enlarged cross-sectional view of the depth stop assembly shown in FIGURE 16;

FIGURE 18 is an enlarged cross-sectional view of the handle assembly shown in FIGURE 16;

FIGURE 19 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 with the depth stop assembly partially advanced along the threaded sleeve;

FIGURE 20 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 with the stylet partially extended from the needle hub;

5 FIGURE 21 is a cross-sectional view of the medical needle shield apparatus as shown in FIGURE 20;

FIGURE 22 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 with the stylet fully extended from the needle hub;

10 FIGURE 23A is an enlarged cross-sectional view of the medical needle shield apparatus as shown in FIGURE 22;

FIGURE 23B is an enlarged cross-sectional view of an alternate embodiment of the medical needle shield apparatus shown in FIGURE 22;

15 FIGURE 24 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 with the stylet removed and a syringe inserted in the needle hub for aspiration purposes;

FIGURE 25 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 with the depth stop assembly removed;

FIGURE 26 is a perspective view of the medical needle shield apparatus shown in FIGURE 16 in the shielded configuration;

20 FIGURE 27 is an enlarged cross-sectional view of the medical needle shield apparatus shown in FIGURE 26;

FIGURE 28 is a perspective view of an embodiment of a medical needle shield apparatus adapted for use with a PICC introducer in accordance with the principles of the present disclosure;

25 FIGURE 29 is an alternative perspective view of an embodiment of a medical needle shield apparatus illustrated in FIGURE 28;

FIGURE 30 is an enlarged cutaway perspective view of the embodiment shown in FIG 28 in a retracted position;

FIGURE 31 is a perspective view of the embodiment shown in FIGURE 28 in a shielded configuration;

5 FIGURE 32 is a cutaway perspective view of the embodiment shown in FIGURE 28 in a shielded configuration;

FIGURE 33 is a cutaway perspective view of the embodiment shown in FIGURE 28 in a reset configuration in accordance with the present disclosure;

10 FIGURE 34 is a perspective view of an embodiment of a medical needle shield apparatus adapted for use with an implanted port access in accordance with the principles of the present disclosure;

FIGURE 35 is a perspective view of the embodiment shown in FIGURE 34 in an unshielded configuration;

15 FIGURE 36 is a cutaway perspective view of the embodiment shown in FIGURE 34 in a shielded configuration;

FIGURE 37 is a cutaway perspective view of the embodiment shown in FIGURE 34 in an unshielded configuration;

20 FIGURE 38 is a perspective view of an embodiment of a medical needle shield apparatus adapted for use with a drug vial access in accordance with the principles of the present disclosure;

FIGURE 39 is a perspective view of the embodiment shown in FIGURE 38 in an unshielded configuration;

FIGURE 40 is cutaway perspective view of the embodiment shown in FIGURE 39 in a shielded configuration; and

25 FIGURE 41 is a cutaway perspective view of the embodiment shown in FIGURE 39 in a reset configuration according to the principles of the present disclosure.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

The exemplary embodiments of the medical needle shield apparatus and methods of operation disclosed are discussed in terms of medical needles for infusion of intravenous fluids, medication infusion or fluid collection, guiding of other needles, e.g.,
5 biopsy, and more particularly, in terms of needle shield apparatus employed with a needle cannula that prevent hazardous exposure to the needle tip, including, for example, inadvertent needle sticks. It is envisioned that the present disclosure, however, finds application to a wide variety of cannula needles and devices for the infusion of preventive medications, medicaments, therapeutics, etc. to a subject, such as, for example, epidural
10 needles, spinal needles, biopsy needles, chiba needles, potts courmand needles, coaxial introducer needles, Y-sites, etc. It is also envisioned that the present disclosure may be employed for collection of body fluids and/or tissues, including those employed during procedures relating to soft tissue biopsy, bone biopsy, phlebotomy, digestive, intestinal, urinary, veterinary, etc. It is contemplated that the medical needle shield apparatus may
15 be utilized with other medical needle applications including, but not limited to, fluid infusion, fluid collection, catheters, catheter introducers, guidewire introducers, biopsy needle introducers, spinal and epidural, biopsy, aphaeresis, dialysis, blood donor, Veress needles, Huber needles, etc.

In the discussion that follows, the term “proximal” refers to a portion of a
20 structure that is closer to a clinician, and the term “distal” refers to a portion that is further from the clinician. As used herein, the term “subject” refers to a patient that receives infusions or has blood and/or fluid collected therefrom using the medical needle shield apparatus. According to the present disclosure, the term “clinician” refers to an individual administering an infusion, performing fluid or tissue collection, installing or
25 removing a needle cannula from a medical needle shield apparatus and may include support personnel.

The following discussion includes a description of the medical needle shield apparatus, followed by a description of the method of operating the medical needle shield apparatus in accordance with the present disclosure. Reference will now be made in

detail to the exemplary embodiments of the disclosure, which are illustrated in the accompanying figures.

Turning now to the figures, wherein like components are designated by like reference numerals throughout the several views. Referring initially to FIGURES 1-11, there is illustrated a medical needle shield apparatus, constructed in accordance with the principals of the present disclosure. The medical needle shield apparatus includes a shield 101 that is extensible from a retracted position (FIGURES 1, 3) to an extended position (FIGURES 2, 4) to enclose a distal end 115 of a needle such as, for example, stylet 106 of a needle assembly. The needle assembly includes a hollow outer needle 103. Stylet 106 is slideably and concentrically disposed with needle 103 for employment therewith during a medical needle application, as will be discussed. A stylet handle 113 is connected to stylet 106 to facilitate manipulation thereof. Other needle assemblies are also contemplated, including for example, needle cannulae, guide wire/introducers, etc.

A binding member 105 is disposed within shield 101 and defines binding surfaces 122. Binding surfaces 122 form an aperture configured for slidable receipt of stylet 106 between the retracted position and the extended position. Binding member 105 includes a drag inducing member, such as, for example, friction members 126 extending therefrom. Binding member 105 has a stylet communicating surface 123 that is engageable with stylet 106 to prevent rotation to the binding position of binding member 105.

Friction members 126 are configured for slidable engagement with stylet 106 between the retracted position and the extended position such that friction members 126 engage stylet 106 to create a drag force with stylet 106. It is envisioned that one or a plurality of friction members 126 may be employed.

The drag force in conjunction with one of blocking members 116 and/or 117, cause binding member 105 to move to a binding position (FIGURE 4). The force created by blocking members 116 and/or 117 acts in a direction opposite to the drag force. This causes a force couple, which moves binding member 105 to the binding position.

As stylet 106 is released from engagement with a stylet communicating surface 123, binding member 105 and a retainer 114 move to the binding position. Rotation of binding member 105 is no longer opposed by engagement with stylet 106 at stylet communicating surface 123. Thus, binding member 105, with retainer 114, is subject to inclination into the binding position. Rotation of binding member 105 causes binding surfaces 122 to frictionally engage stylet 106 to prevent movement thereof.

Blocking members 116 and/or 117 cause binding member 105 to move to the binding position as forces imposed on shield 101 cause relative movement thereof in either direction along longitudinal axis x . This maintains stylet 106 within shield 101 to avoid hazardous exposure to distal end 115. It is envisioned that stylet communicating surface 123 may include ribs, projections, cavities, etc. for engagement with stylet 106 or that a portion of stylet communicating surface 123 engages stylet 106.

The components of the medical needle shield apparatus can be fabricated from a material suitable for medical applications, such as, for example, polymeric or metals, such as stainless steel, depending on the particular medical application and/or preference of a clinician. Semi-rigid and rigid polymeric are contemplated for fabrication, as well as resilient materials, such as molded medical grade polypropylene. However, one skilled in the art will realize that other materials and fabrication methods suitable for assembly and manufacture, in accordance with the present disclosure, also would be appropriate.

In an illustrative embodiment, shield 101 includes a bearing 102 that houses binding member 105. Bearing 102 may be monolithically formed or integrally assembled of multiple sections and may be substantially transparent, opaque, etc.

In the retracted position, shield 101 is disposed adjacent to a needle hub 104 of outer needle 103. It is contemplated that outer needle 103 may also be comprised of a flexible, polymeric material, and that the components of the medical needle apparatus may be employed with other needle applications, such as, for example, catheters, PICC introducers, etc.

Binding member 105 may be monolithically formed and includes an aperture plate 118, frictional members 126, end sensing member 119, stylet communicating surface 123, binding member reset surface 107 and retainer 114. It is contemplated that binding member 105 may include one or more frictional members 126, and that retainer
5 114 may extend from bearing 102. Aperture plate 118 may have a rectangular, generally planar configuration with sufficient stiffness to produce forces for binding stylet 106, as will be discussed. It is envisioned that aperture plate 118 may have an arcuate surface, undulating, etc. It is further envisioned that aperture plate 118 may have various degrees of stiffness according to the requirements of a particular application.

10 The embodiment of a resettable passive safety device disclosed in FIGURES 1-11 show a hollow needle 103 solid stylet 106, rotational housing with a stylet shield 125 and thrust bore 133, a bearing 102 with thrust collar 132, and a binding member 105. The thrust bore 133 and thrust collar 132 are configured to allow rotation of stylet shield 125 relative to bearing 102.

15 The resettable feature of this device is employed after the passive safety device has been activated. Initially, the safety shield 101 and needle 103 are positioned over the stylet 106 (FIGURE 1). During the medical procedure, the stylet 106 is automatically protected by the safety shield 101 as the stylet 106 is withdrawn from the needle (FIGURE 2).

20 The safety shield 101 is advanced to near the distal end of the stylet 115 in a position prior to activation of the binding member 105 (FIGURE 3). In this position, the hub retainer 114 retains the proximity of the needle hub 104 to the safety shield 101 by interacting with hub slot 124 and the binding member 105 is in the sliding orientation. It is envisioned that hub slot 124 may be in the form of other shapes for providing a cavity.

25 In FIGURE 4, the safety shield 101 is positioned further toward the distal end of the stylet 115 to the point where the safety shield 101 is activated. The binding member 105 has moved to the binding orientation and the hub retainer 114 of the binding member 105 has released the needle hub 104.

In FIGURE 2, the activated and locked safety shield 101 is illustrated. In this configuration, the needle 103 has been removed, the stylet distal end 115 is inside the housing at a distance which prevents human contact, and the binding member 105 is in the binding orientation.

5 Frictional members 126 may be monolithically formed with binding member 105 and extend from aperture plate 118 in association therewith for alignment with aperture 138 and engagement with stylet 106. Such engagement creates a frictional drag force with stylet 106. This frictional drag force in conjunction with one of the blocking members 116 and/or 117 causes binding member 105 to move with stylet 106, which
10 generates a canting force and inclination of aperture plate 118. The canting force and inclination urge rotation of binding member 105. It is contemplated that a single friction member may be employed. It is further contemplated that frictional members 126 may have flexible portions, which may be of varying flexibility according to the particular requirements of a needle application.

15 As facilitated by movement of stylet 106, the canting force causes a lever or moment of end sensing member 119, which is opposed to prevent rotation of binding member 105. The canting force is opposed by engagement of stylet communicating surface 123 with stylet 106 in a non-binding or sliding orientation (FIGURE 3) of binding member 105.

20 End sensing member 119 extends distally from aperture plate 118. End sensing member 119 may be perpendicularly oriented relative to a plane defined by aperture plate 118. This perpendicular orientation facilitates inclination of aperture plate 118 for disposal in a binding or non-binding orientation of binding member 105. It is envisioned that end sensing member 119 may be variously oriented with aperture plate 118 and may
25 flexibly extend therefrom.

 Stylet communicating surface 123 opposes the canting force of end sensing member 119 directed to stylet 106. The canting force is generated by friction members 126 in conjunction with one of blocking members 116 and/or 117 and facilitates inclination of aperture plate 118. Inclination, however, is prevented in the non-binding or
30 sliding orientation because of the engagement of stylet communicating surface 123 with

stylet 106. As stylet 106 is retracted proximally and shield 101 is extended distally, stylet 106 continues to slideably engage stylet communicating surface 123.

As stylet 106 is released from engagement with stylet communicating surface 123, as shown in FIGURE 4, a drag force is created between friction members 126 and stylet 106. The drag force in conjunction with blocking member 116, cause aperture plate 118 to move to the binding position, as discussed.

Rotation of aperture plate 118 causes binding surfaces 122 to frictionally engage stylet 106 to prevent movement thereof. Blocking members 116, 117 cause aperture plate 118 to move to the binding position as forces are imposed on shield 101 in either direction along longitudinal axis x . This maintains stylet 106 within shield 101 to avoid hazardous exposure to distal end 115.

Aperture 138 is formed within aperture plate 118 for slidable engagement with stylet 106 during movement between the retracted position and the extended position of shield 101. Aperture 138 includes binding surfaces 122 formed on opposing sides of aperture 138 that engage stylet 106 to prevent movement thereof in the extended position of shield 101. It is contemplated that engagement to prevent movement of stylet 106 may include penetrating, frictional, interference, etc. It is envisioned that aperture 138 may have various geometric configurations, such as radial, polygonal, etc. It is further envisioned that aperture 138 may define an open cavity within aperture plate 118, such as, for example, "U" shaped and open to one or a plurality of edges of aperture plate 118.

The inclination of aperture plate 118 relative to longitudinal axis x facilitates sliding and binding, via binding surfaces 122, of stylet 106 within shield 101 to prevent hazardous exposure to distal end 115. For example, as shown in FIGURE 3, aperture plate 118 is oriented at an angle of approximately 90° relative to longitudinal axis x such that aperture plate 118 is disposed substantially perpendicular to stylet 106. In this non-binding or sliding orientation, stylet 106 is free to slide within aperture 138. As stylet 106 is retracted and shield 101 is extended, stylet 106 continues to engage stylet communicating surface 123 and aperture plate 118 maintains its perpendicular orientation relative to longitudinal axis x .

Referring to FIGURE 4, shield 101 is manipulated such that friction members 126 in conjunction with blocking member 116 cause binding member 105 to rotate relative to longitudinal axis x . Aperture plate 118 rotates out of perpendicular alignment with stylet 106 such that aperture plate 118 is oriented at an angle less than 90° with respect to longitudinal axis x .

As aperture plate 118 rotates, the binding member 105 approaches a binding orientation. The binding orientation includes engagement of binding surfaces 122 with stylet 106 due to the binding orientation of aperture plate 118. This engagement creates binding frictional forces on stylet 106, in conjunction with frictional members 126 and blocking members 116, 117 to prevent movement of stylet 106 relative to shield 101 in both distal and proximal directions, and to maintain distal end 115 within shield 101 to prevent hazardous exposure thereto.

Blocking members 116, 117 are disposed not to interfere with stylet 106. Blocking members 116, 117 define surfaces that facilitate disposal of aperture plate 118 in a binding orientation.

For example, as shown in FIGURE 3, shield 101 is in a retracted position and stylet 106 is fully extended. Binding member 105 and aperture plate 118 are in a non-binding or sliding orientation such that aperture plate 118 is substantially perpendicular to longitudinal axis x . Blocking members 116, 117 may engage aperture plate 118 to maintain aperture plate 118 in the perpendicular orientation. Blocking members 116, 117 may also maintain such orientation during extension of stylet 106 or may not engage stylet 106.

As stylet 106 is retracted and shield 101 is extended, as shown in FIGURE 4, friction members 126 create a drag force via engagement with stylet 106 on binding member 105 and in conjunction with blocking member 116 cause aperture plate 118 to rotate in a counter-clockwise direction to the binding position. Blocking members 116, 117 engage aperture plate 118 to facilitate rotation thereof from the perpendicular position into the binding position such that binding surfaces 122 engage stylet 106, as discussed. This configuration prevents movement of stylet 106.

Binding of binding member 105 to stylet 106 is facilitated by the friction force generated between binding surfaces 122 and stylet 106. This frictional engagement prevents axial movement of stylet 106 relative to bearing 102 when shield 101 is in the extended position. This configuration advantageously prevents hazardous exposure to stylet 106. It is contemplated that binding surfaces 122 may include sharp edges to increase frictional engagement. It is further contemplated that the binding friction force may be created and varied by one or more altering factors, such as, for example, aperture 138 configuration and dimension, stylet 106 configuration and dimension, aperture plate 118 thickness, the dimension from blocking members 116, 117 contact point to the centerline of stylet 106 and the coefficient of friction between aperture 138 and stylet 106 depending on the particular requirements of a needle application. It is envisioned that friction members 126 may be configured so as to vary the drag force with variation of the inclination of the aperture plate 118, this variation in drag force may be accomplished by geometric changes in the shape of the friction members 126, such as wedge shapes or the inclusion of notches to engage stylet 106, this variation in drag force may also be accomplished through the selective application of friction modifying materials or coatings such as oils, jells, greases, or coatings which change the friction.

It is envisioned that the aperture in aperture plate 118 may create a drag force via engagement with stylet 106 to cause rotation of binding member 105, similar to that described. It is further envisioned that materials such as, for example, jells, greases, etc. may be employed to create a frictional drag force with stylet 106 to cause rotation of binding member 105.

Needle hub 104 is mounted with needle 103 and is releasably mounted with shield 101 via releasable engagement with retainer 114. Needle hub 104 is employed with the medical needle shield apparatus of the present disclosure for various utility according to the requirements of a particular medical needle application. Shield 101 and needle hub 104 slidably support needle 103 and stylet 106 for use thereof. Handle 113 facilitates manipulation thereof.

Needle hub 104 has a hub slot 124 for receipt and engagement with binding member 105. Needle hub 104 has a finger tab 160 for urging needle hub 104 in a

direction, along longitudinal axis x , away from shield 101. This configuration facilitates removal and use of needle hub 104 and needle 103 from shield 101 during a medical needle application. It is contemplated that finger tab 160 may be alternatively configured and dimensioned according to the needle application.

5 A flange 162 of needle hub 104 is concentrically supported by a control surface 110 disposed about an inner surface of bearing 102. Control surface 110 engages an outer surface 164 of flange 162 for releasable support thereof. Outer surface 164 may engage control surface 110 in a frictional, interference, etc. fit to maintain releasable positioning with bearing 102. It is contemplated that control surface 110 may engage
10 other portions of needle hub 104.

Bearing 102 includes hub stop surfaces 112 that facilitate positioning of needle hub 104 with bearing 102. Hub stop surfaces 112 prevent proximal movement of needle hub 104 during mounting with and relative to bearing 102. Hub stop surfaces 112 advantageously facilitate control of the degree of insertion with bearing 102 according to
15 the requirements of a particular medical needle application. One or a plurality of hub stop surfaces 112 may be employed. It is contemplated that hub stop surfaces 112 may include springs, clips, etc. to facilitate attachment with needle hub 104.

Retainer 114 may extend transversely from a distal end of stylet communicating surface 123. Hub retainer 114 extends a sufficient length for corresponding receipt
20 within hub slot 124 of needle hub 104. In association with a non-binding or sliding orientation of binding member 105, retainer 114 engages needle hub 104, in hub slot 124, for releasably mounting with bearing 102 of shield 101.

As stylet 106 is retracted in a proximal direction and shield 101 is extended in a distal direction, retainer 114 rotates in a counter clockwise direction (FIGURE 4) relative
25 to longitudinal axis x due to the canting forces generated by friction members 126. Retainer 114 disengages from hub slot 124 to release needle hub 104 from bearing 102. A clinician may manipulate finger tab 160 to manipulate needle hub 104 distally and apart from shield 101. It is contemplated that retainer 114 may be variously oriented from binding member 105 or stylet communicating surface 123. It is further
30 contemplated that hub slot 124 may be variously dimensioned to extend about the

circumference of needle hub 104. Hub slot 124 may include tabs, etc. for retention with retainer 114.

To re-access the stylet distal end 115 using the resettable passive safety device, the stylet shield 125 is brought to mate concentrically with the proximal end of the needle hub 104, in a similar fashion to the pre-activated state of the device. As this occurs, the binding member reset surface 107 comes into contact with the hub reset surface 108. This action is depicted in the embodiment shown in FIGURE 10.

As the stylet 106 is advanced from a proximal-to-distal direction, the hub reset surface 108 deflects the binding member reset surface 107, along with the end sensing member 119, to a position above the stylet 106 surface and urges the binding member 105 from the binding orientation to the sliding orientation. With the binding member 105 in the sliding orientation, the stylet 106 becomes free to advance into the needle 103.

Concurrently, due to the contact between the hub reset surface 108 and the binding member reset surface 107, the hub retainer 114 is urged into the hub slot 124. This causes the hub retainer 114 of the binding member 105 to again retain the needle hub 104 to the safety shield 101 through the interaction with the hub slot 124 (FIGURE 11).

Upon being reset, the safety shield 101 and needle 103 are positioned over the stylet 106, as seen in FIGURE 1. During the medical procedure, the stylet 106 will be automatically protected by the safety shield 101 as the stylet 106 is again withdrawn from the needle.

FIGURES 12 – 15 illustrate the resettable safety shield according to the present disclosure as applied to a needle with a luer fitting 121 and a luer taper 109. In this embodiment, the hub reset surface 108 is provided on a portion separate from the needle hub 104. A hub reset surface spring 111 exerts a force to bias the hub reset surface 108 in the proximal direction. The hub reset surface spring 111 can be made from any number of suitable resilient materials commonly known, including metal, plastic, elastomeric materials, and the like.

In the embodiment wherein the hub reset surface 108 is within the luer fitting 121, the hub reset surface spring 111 assures that the hub reset surface 108 is in the correct location in the needle hub to provide alignment and engagement between the hub reset surface 108 and binding member reset surface 107. When a luer male taper, such as for example, a luer lock or luer slip is inserted into needle hub 104, the hub reset surface spring 111 is compressed and the hub reset surface 108 is displaced to allow the luer male taper to mate with the entire length of luer taper 109. It is envisioned that the hub reset surface 108 may also be disposed around the luer fitting 121, as shown in FIGURE 23B. The embodiment shown in FIGURE 23B also shows an alternate embodiment of the reset surfaces 107 extending from the binding member 105 and engaging retaining surface 141.

To re-access the stylet distal end 115 using the resettable passive safety device, the stylet shield 125 is brought to mate concentrically with the proximal end of the needle hub 104, in a similar fashion to the pre-activated state of the device. As this occurs, the binding member reset surface 107 comes into contact with the hub reset surface 108. This action is depicted in the embodiment shown in FIGURE 14.

As the stylet 106 is advanced from a proximal-to-distal direction, the hub reset surface 108 deflects the binding member reset surface 107, along with the end sensing member 119, to a position above the stylet 106 surface and urges the binding member 105 from the binding orientation to the sliding orientation. With the binding member 105 in the sliding orientation, the stylet 106 becomes free to advance into the needle 103.

Concurrently, due to the contact between the hub reset surface 108 and the binding member reset surface 107, the hub retainer 114 is urged into the hub slot 124. This causes the hub retainer 114 of the binding member 105 to again retain the needle hub 104 to the safety shield 101 through the interaction with the hub slot 124 (FIGURE 15).

Upon being reset, the safety shield 101 and needle 103 are positioned over the stylet 106. During the medical procedure, the stylet 106 will be automatically protected by the safety shield 101 as the stylet 106 is again withdrawn from the needle.

FIGURES 16-27 illustrate the resettable safety shield according to the present disclosure as applied to a bone biopsy needle 101. In this embodiment, the luer taper 109 is used in the manner described hereinbefore with respect to FIGURES 12 – 15. The bone biopsy needle 101 may also include an adjustable depth stop assembly 140 for
5 setting the desired needle 103 insertion depth. A lock nut 142 locks the depth stop assembly 140 in the desired position. Tabs 144 engage corresponding slots 156 (shown in FIGURE 25) to fix depth stop assembly 140 while the lock nut 142 is engaged.

A needle shield 137 may be disposed in depth stop assembly 140 as illustrated in FIGURE 17. Corresponding threads 148 and 150 disposed on depth stop assembly 140
10 and sleeve 151, respectively, provide for threadable movement of depth stop assembly 140. Needle shield 137 operates in similar fashion to shield 101 described in FIGURES 1-11, as will be discussed in more detail hereafter.

The medical needle shield apparatus for stylet 106 includes a binding member 105 that is disposed within a stylet shield 125, similar to that described with regard to
15 FIGURES 1-11, that is extensible from a retracted position to an extended position to enclose a distal end of a stylet 106 of a needle assembly. Stylet 106 is slideably and concentrically disposed with a needle 103 of the needle assembly for employment therewith during a bone biopsy needle application. A stylet handle 113 is connected to stylet 106.

20 In operation, the clinician (not shown) manipulates handle 113 such that shield 101 is in the retracted position (FIGURES 16, 18, 19) and binding member 105 is in a non-binding or sliding position. Handle 113 may include a tab 152 for temporary securement to hub 104. Hub 104 includes an opening (not shown) such that handle 113 may be released from temporary securement as tab 152 is rotated to align tab 152 with
25 the opening. Stylet 106 is extended relative to shield 101 such that needle hub 104 is disposed about needle 103 and needle hub 104 is releasably mounted with bearing 102. A procedure employing the medical needle shield apparatus with stylet 106 and needle 103 is performed by the clinician to completion.

Needle hub 104 is releasably mounted with stylet handle 113. Referring to
30 FIGURE 22, stylet 106 is retracted proximally such that shield 101 is extended to the

extended position and binding member 105 is disposed in a binding position. Needle hub 104 is released from stylet shield 125 in the extended position. This maintains stylet 106 within stylet shield 125 to avoid hazardous exposure to the distal end of stylet 106.

To re-access the stylet distal end 115 using the resettable passive safety device, the stylet shield 125 is brought to mate concentrically with the proximal end of the needle hub 104, in a similar fashion to the pre-activated state of the device. As this occurs, the binding member reset surface 107 comes into contact with the hub reset surface 108. This action is depicted in the embodiment shown in FIGURE 23A.

As the stylet 106 is advanced from a proximal-to-distal direction, the hub reset surface 108 deflects the binding member reset surface 107, along with the end sensing member 119, to a position above the stylet 106 surface and urges the binding member 105 from the binding orientation to the sliding orientation. With the binding member 105 in the sliding orientation, the stylet 106 becomes free to advance into the needle 103.

Concurrently, due to the contact between the hub reset surface 108 and the binding member reset surface 107, the hub retainer 114 is urged into the hub slot 124. This causes the hub retainer 114 of the binding member 105 to again retain the needle hub 104 to the safety shield 101 through the interaction with the hub slot 124.

Upon being reset, the stylet shield 125 and needle 103 are positioned over the stylet 106, as seen in FIGURE 16. During the medical procedure, the stylet 106 will be automatically protected by the stylet shield 125 as the stylet 106 is again withdrawn from the needle.

FIGURE 24 illustrates a syringe inserted into hub 104 for aspiration purposes with stylet 106 removed.

FIGURE 25 illustrates the resettable safety shield device 101 with the depth stop assembly 140 removed and the needle shield 137 in the retracted position. FIGURES 26-27 show the needle shield 137 in the shielded configuration. A binding member 105' is disposed within needle shield 137 and defines binding surfaces (not shown). Binding surfaces form an aperture configured for slidable receipt of hollow needle 103 between the retracted position and the extended position. Binding member 105' includes a drag

inducing member, such as, for example, friction members 126' extending therefrom. Binding member 105' has a needle communicating surface 123' that is engageable with hollow needle 103 to prevent rotation of binding member 105'.

Friction members 126' are configured for slidable engagement with hollow needle
5 103 between the retracted position and the extended position such that friction members 126' engage hollow needle 103 to create a drag force with hollow needle 103. It is envisioned that one or a plurality of friction members 126' may be employed.

The drag force in conjunction with one of blocking members 116' and/or 117',
cause binding member 105' to move to a binding position (FIGURE 27). The force
10 created by blocking members 116' and/or 117' acts in a direction opposite to the drag force. This causes a force couple, which moves binding member 105' to the binding position.

A funnel portion 146 in needle shield 137 acts as a probe guide to facilitate
insertion of a shepherd's hook or the like. Depth stop 140 may be slideably removed
15 with safety shield 137 remaining in the proximal position. This allows a clinician to utilize the entire length of needle 103. As shown, depth stop 140 is removed prior to activation of safety shield 137. Alternatively, safety shield 137 may be connect to, or formed as part of, the depth stop 140.

FIGURES 28-29 illustrate the resettable safety shield device according to the
20 present disclosure as applied to a PICC introducer or similar catheter and needle introducers. In this embodiment, the hollow needle 103 is polymeric, and the stylet (or inner needle) 106 is a sharp, hollow bore cannula. The handle 113 of the PICC Introducer has a flash plug 135 and a flash chamber 136 that is in communication with inner needle 106. A luer fitting 121 communicates with the flash chamber 136 and
25 allows the fitting of other medical devices.

The medical needle shield apparatus includes a shield 101, similar to those described, that is extensible from a retracted position (FIGURE 28) to an extended position (FIGURES 31-32) to enclose a distal end of hollow needle 103 of a needle assembly. Hollow needle 103 is slideably and concentrically disposed with a hub 104

(FIGURE 28) of the needle assembly for employment therewith during a PICC introducer application. Hub 104 may, or may not, be splittable. Hub 104 is desirably fabricated from a polymeric material. It is contemplated that the medical needles of the present disclosure may incorporate a protective needle sheath member to facilitate additional protection during transportation and use of the medical needles.

A handle 113 is connected to inner needle 106. Handle 113 may have a flash chamber 139 in communication with inner needle 106. A luer fitting 121 communicates with flash chamber 139 that facilitates connection to various medical devices via either a luer slip or luer lock attachment feature.

A binding member 105, similar to that described with regard to FIGURES 1-11, is disposed within shield 101. Shield 101 includes a bearing 102 that houses binding member 105.

Needle hub 104 is mounted with hollow needle 103. Needle hub 104 is releasably mounted with shield 101 via releasable engagement with a retainer 114 of binding member 105. Needle hub 104 has a hub slot 124 for receipt and engagement with binding member 105. This configuration facilitates removal and use of hub 104 from shield 101 during a medical needle application.

A flange of needle hub 104 is concentrically supported by a control surface of a stylet shield 125, discussed below. The control surface engages the flange for releasable support thereof. Retainer 114 extends for receipt within a hub slot 124 of needle hub 104. In association with a non-binding or sliding orientation of binding member 105, retainer 114 is disposed within hub slot 124 for releasably mounting with shield 101. As inner needle 106 is retracted and shield 101 is extended, retainer 114 rotates in a counter clockwise direction and disengages from hub slot 124 to release needle hub 104 from stylet shield 125.

A stylet shield 125 is disposed for rotation and enclosure of the distal end of inner needle 106. Stylet shield 125 is mounted with handle 113 and freely rotates relative to shield 101 and inner needle 106 in the extended position of shield 101. Relative rotation of stylet shield 125 is facilitated by support at bearing openings formed in stylet shield

125 and axles, similar to those described above. In a binding position, the bearing configuration supports rotation of stylet shield 125 relative to shield 101 and inner needle 106.

5 Inner needle 106 is retracted proximally such that shield 101 is extended to the extended position and binding member 105 is disposed in a binding position. Needle hub 104 is released from shield 101 and shield 101 encloses the distal end of needle 103 in the extended position. This maintains needle 103 within shield 101 to avoid hazardous exposure to the distal end of needle 103.

10 In operation, needle hub 104 is released from shield 101 and a stylet shield 125 encloses the distal end of inner needle 106 in the extended position, as described above. This maintains inner needle 106 within shield 101 to avoid hazardous exposure to the distal end thereof.

15 To re-access the inner needle 106 using the resettable passive safety device, the stylet shield 125 of the rotating focusing is brought to mate concentrically with the proximal end of the needle hub 104, in a similar fashion to the pre-activated state of the device. As this occurs, the binding member reset surface 107, on the end sensing member 119, comes into contact with the hub reset surface 108. This action is depicted in the embodiment shown in FIGURES 30 and 33.

20 As the inner needle 106 is advanced from a proximal-to-distal direction, the hub reset surface 108 deflects the binding member reset surface 107, along with the end sensing member 119, to a position above the inner needle 106 surface and urges the binding member 105 from the binding orientation to the sliding orientation. With the binding member 105 in the sliding orientation, the inner needle 106 becomes free to advance into hollow needle 103.

25 Concurrently, due to the contact between the hub reset surface 108 and the binding member reset surface 107, the hub retainer 114 is urged into the hub slot 124. This causes the hub retainer 114 of the binding member 105 to again retain the needle hub 104 to the safety shield 101 through the interaction with the hub slot 124.

Upon being reset, the safety shield 101 and hollow needle 103 are positioned over the inner needle 106, as seen in FIGURE 28. During the medical procedure, the inner needle 106 will be automatically protected by the safety shield 101 as the inner needle 106 is again withdrawn from the needle.

5 FIGURES 34-37 illustrate the resettable safety shield device according to the present disclosure as applied to a port access device or implanted pump. It is contemplated herein that the port access device may be implanted or exterior to a patient. Operation and construction of this embodiment is in accordance with the various embodiments described herein such as for example the embodiments disclosed in
10 FIGURES 1-11. FIGURES 34 – 37 show an implanted port 127 and skin layer 129 along with an implanted port access body 130. The port access body contains the hub reset surface 108. In the present embodiment, the stylet 106 is protected by the safety shield 101 before use. Hub reset surface 108 and binding member reset surface 107 reset the safety device as described hereinbefore to allow stylet 106 to pass through the skin layer
15 129 and enter the implanted port 127. The safety shield device reactivates upon removal of stylet 106 from the implanted port access body 130.

With reference to FIGURES 38-41, illustrated is a resettable safety shield device according to the present disclosure as applied to a drug vial access. Operation and construction of this embodiment is in accordance with the various embodiments
20 described herein such as for example the embodiments disclosed in FIGURES 1-11. FIGURES 38 – 41 show a drug vial 131 along with a corresponding drug vial access body 134. Stylet 106 is protected by a safety shield 101 before use. Hub reset surface 108 engages binding member reset surface 107 to allow stylet 106 to enter drug vial 131. The safety device re-activates upon removal of stylet 106 from drug vial access body
25 134.

The invention of the present disclosure may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than

by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

WHAT IS CLAIMED IS:

1. A medical needle shield apparatus comprising:

a needle hub having an outer needle cannula extending therefrom to a distal end, an inner needle being disposed for slidable movement with the outer needle cannula; and

5 at least one shield being extensible from a retracted position to an extended position to enclose a distal end of the inner needle,

the shield including a binding member disposed within the shield and defining binding surfaces that form an aperture configured for slidable receipt of the inner needle between the retracted position and the extended position,

10 the binding member including at least one drag inducing member such that the at least one drag inducing member engages the inner needle during slidable receipt of the inner needle to create a drag force with the inner needle, the drag force and shield facilitating rotation of the binding member relative to a longitudinal axis of the inner needle such that the binding surfaces engage the inner needle to prevent slidable
15 movement of the inner needle in the extended position of the shield,

the binding member further including a needle communicating surface extending therefrom such that the needle communicating surface is engageable with the inner needle to prevent rotation of the binding member,

a retainer for releasable engagement with the needle hub, and

20 the binding member further including a binding member reset surface aligned with a hub reset surface.

2. A medical needle shield apparatus as recited in claim 1, wherein the at least one drag inducing member defines a cavity that is substantially aligned with the aperture, the cavity being configured for slidable receipt of the needle to create the drag
25 force with the needle.

3. A medical needle shield apparatus as recited in claim 1, wherein the binding member includes a substantially planar aperture plate that includes the binding surfaces that form the aperture.

4. A medical needle shield apparatus as recited in claim 3, wherein the at least one drag inducing member includes a pair of arms extending from the aperture plate.

5. A medical needle shield apparatus as recited in claim 3, wherein the arm
5 includes a deflectable member.

6. A medical needle shield apparatus as recited in claim 1, wherein the binding member is rotatable, relative to a longitudinal axis of the inner needle, between a non-binding orientation whereby the inner needle is slidable relative to the binding member and a binding orientation whereby the binding surfaces engage the inner needle
10 to prevent slidable movement of the inner needle in the extended position of the at least one shield.

7. A medical needle shield apparatus as recited in claim 1, wherein the shield includes a housing that defines at least one blocking member extending from an interior surface thereof, the at least one blocking member being engageable with the binding
15 member for urging the binding member to a binding orientation.

8. A medical needle shield apparatus as recited in claim 3, wherein the shield includes a housing that defines at least one blocking member extending from an interior surface thereof, the aperture plate being axially movable for engagement with the at least one blocking member that causes rotation of the binding member to a binding orientation.

20 9. A medical needle shield apparatus as recited in claim 1, wherein the at least one shield is supported for relative rotational movement by at least one bearing.

10. A medical needle shield apparatus as recited in claim 1, wherein the inner needle is attached to a handle for manipulation thereof.

11. A medical needle shield apparatus as recited in claim 1, wherein the
25 needle hub is releasably mountable with a housing of the at least one shield.

12. A medical needle shield apparatus as recited in claim 1, wherein the needle hub defines a hub slot that is configured to receive the retainer of the binding member.

13. A medical needle shield apparatus as recited in claim 1, wherein the binding member includes at least one outwardly arcuate arm that extends to the needle communicating surface.

14. A medical needle shield apparatus as recited in claim 1, further comprising
5 a plurality of shields.

15. A medical needle shield apparatus as recited in claim 1, wherein said binding member reset surface comprises the distal facing surface of said retainer.

16. A medical needle shield apparatus as recited in claim 1, wherein said hub reset surface is configured to deflect said binding member reset surface to facilitate
10 rotation of the binding member relative to said longitudinal axis such that said binding surface disengages the inner needle.

17. A medical needle shield according to claim 1, wherein said medical needle is adapted for bone biopsy.

18. A medical needle shield according to claim 1, wherein said medical needle
15 is adapted for catheter introduction to a patient.

19. A medical needle shield apparatus as recited in claim 1, wherein said hub reset surface is separate from said hub and urged by a spring toward said binding member reset surface.

20. A medical needle shield apparatus of claim 19, further comprising a luer
20 male taper configured with said hub.

21. A medical needle shield according to claim 1, wherein said medical needle operates in communication with a port access device.

22. A medical needle shield according to claim 1, further comprising a protective needle sheath member.

25 23. A medical needle shield apparatus comprising:

a needle hub having an outer needle cannula extending therefrom, an inner needle being disposed for slidable movement with the outer needle cannula; and

a shield being extensible from a retracted position to an extended position to enclose a distal end of the outer needle cannula,

the shield including a binding member disposed within the shield and defining binding surfaces that form an aperture configured for slidable receipt of the outer needle cannula between the retracted position and the extended position,

the binding member including at least one drag inducing member such that the at least one drag inducing member engages the outer needle cannula during slidable receipt of the outer needle cannula to create a drag force with the outer needle cannula, the drag force and shield facilitating rotation of the binding member relative to a longitudinal axis of the outer needle cannula such that the binding surfaces engage the outer needle cannula to prevent slidable movement of the outer needle cannula in the extended position of the shield, and

the binding member further including a needle communicating surface extending therefrom such that the needle communicating surface is engageable with the outer needle cannula to prevent rotation of the binding member.

24. A medical needle shield apparatus as recited in claim 23, wherein the binding member is rotatable, relative to a longitudinal axis of the outer needle cannula, between a non-binding orientation whereby the outer needle cannula is slidable relative to the binding member and a binding orientation whereby the binding surfaces engage the outer needle cannula to prevent slidable movement of the outer needle cannula in the extended position of the shield.

25. A medical needle shield apparatus as recited in claim 23, wherein the shield includes a housing that defines at least one blocking member extending from an interior surface thereof, the binding member including an aperture plate being axially movable for engagement with the at least one blocking member that causes rotation of the binding member to a binding orientation.

26. A medical needle shield apparatus as recited in claim 23, wherein the shield includes a probe guide at a distal end thereof configured for receipt of a probe, the probe being configured for slidable movement with the outer needle cannula.

27. A medical needle shield apparatus comprising:

a needle hub having an outer needle cannula extending therefrom to a distal end, an inner needle being disposed for slidable movement with the outer needle cannula, a handle being attached to the inner needle; and

5 a shield being releasably mountable to the needle hub and extensible from a retracted position to an extended position to enclose a distal end of the inner needle, the handle being disposed adjacent the shield,

the shield including a binding member disposed within the shield and defining binding surfaces that form an aperture configured for slidable receipt of the inner needle
10 between the retracted position and the extended position,

the binding member including at least one drag inducing member such that the at least one drag inducing member engages the inner needle during slidable receipt of the inner needle to create a drag force with the inner needle, the drag force and shield facilitating rotation of the binding member relative to a longitudinal axis of the inner
15 needle such that the binding surfaces engage the inner needle to prevent slidable movement of the inner needle in the extended position of the shield, and

the binding member further including a needle communicating surface extending therefrom such that the needle communicating surface is engageable with the inner needle to prevent rotation of the binding member, a retainer for releasable engagement
20 with a hub slot of the needle hub, and a binding member reset surface aligned for engagement with a hub reset surface.

28. A medical needle shield apparatus as recited in claim 27, wherein the binding member is rotatable, relative to a longitudinal axis of the inner needle, between a non-binding orientation whereby the inner needle is slidable relative to the binding
25 member and a binding orientation whereby the binding surfaces engage the inner needle to prevent slidable movement of the inner needle in the extended position of the shield.

29. A medical needle shield apparatus as recited in claim 27, wherein the shield includes a housing that defines at least one blocking member extending from an interior surface thereof, the binding member including an aperture plate being axially

movable for engagement with the at least one blocking member that causes rotation of the binding member to a binding orientation.

30. A medical needle shield apparatus as recited in claim 27, further comprising a luer slip or luer lock attachment feature.

5 31. A medical needle shield apparatus as recited in claim 27, further comprising a flash chamber in communication with the inner needle, the flash chamber having a fitting that facilitates connection to a medical device.

32. A medical needle shield apparatus comprising:

a needle hub having a needle cannula extending therefrom to a distal end;

10 at least one shield being extensible from a retracted position to an extended position to enclose a distal end of the needle cannula; and

a depth stop device slidably disposed on the needle cannula, said at least one shield being substantially disposed within said depth stop device.

33. A medical needle shield apparatus comprising:

15 a needle hub having an outer needle cannula extending therefrom to a distal end, an inner needle being disposed for slidable movement with the outer needle cannula; and

at least one shield being extensible from a retracted position to an extended position to enclose a distal end of the inner needle,

20 the needle shield further including a reset surface aligned with a hub reset surface for engagement therewith to allow reuse of the shield in a shielded configuration.

ABSTRACT OF THE DISCLOSURE

5 A medical needle shield apparatus is provided that includes a needle hub having an outer needle cannula extending therefrom. An inner needle is disposed for slidable movement with the outer needle cannula. At least one shield is extensible from a retracted position to an extended position to enclose a distal end of the inner needle. The shield includes a binding member disposed within the shield and defines binding surfaces that form an aperture configured for slidable receipt of the inner needle. The binding member includes a binding member reset surface aligned with a hub reset surface for engagement therewith to allow reuse of a shielded needle apparatus.

10




FIGURE 1




FIGURE 2

3/42




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12

13/42




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16

17/42




FIGURE 17




FIGURE 18




FIGURE 19




FIGURE 20

21/42




FIGURE 21




FIGURE 22




FIGURE 23A




FIGURE 23B




FIGURE 24

26/42




FIGURE 25

27/42




FIGURE 26




FIGURE 27




FIGURE 28




FIGURE 29




FIGURE 30




FIGURE 31




FIGURE 32




FIGURE 33




FIGURE 34




FIGURE 35




FIGURE 36




FIGURE 37

39/42




FIGURE 38




FIGURE 39




FIGURE 40




FIGURE 41

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor(s), I hereby declare that:

TYPE OF DECLARATION

This declaration is for a **UTILITY** patent application.

INVENTORSHIP IDENTIFICATION

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if two or more names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

RESETTABLE SAFETY SHIELD FOR MEDICAL NEEDLES

SPECIFICATION IDENTIFICATION

The specification

- ☒ is attached hereto.
☐ was filed on _____ and has U.S. Application Number _____,
and was amended on _____.

ACKNOWLEDGMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, Section 1.56.

PRIORITY

The present application claims the benefit under 35 U.S.C. §120 of the following Applications:

Application Serial Number	Filing Date	Status
09/809,357	March 15, 2001	Pending
10/202,201	July 23, 2002	Pending
60/424,655	November 7, 2002	Pending
10/322,288	December 17, 2002	Pending
10/409,819	April 8, 2003	Pending

POWER OF ATTORNEY

I hereby appoint the following practitioner(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

APPOINTED PRACTITIONER(S)

Paul S. Evans, Reg. No. 36,130

of Specialized Health Products International, Inc., 585 West 500 South, Bountiful, Utah 84010;

Mark S. Leonardo, Reg. No. 41,433

Peter B. Sorell, Reg. No. 44,349

John C. Serio, Reg. No. 39,238

Joseph P. Quinn, Reg. No. 45,029

Brian L. Michaelis, Reg. No. 34,221

John J. Penny, Jr., Reg. No. 36,984

Barry C. Nelson, Reg. No. 46,951

David D. Lowry, Reg. No. 38,538

Mark A. Hofer, Reg. No. 30,068

Lucy Elandjian, Reg. No. 46,164

Maria Eliseeva, Reg. No. 43,328

all of Brown Rudnick Berlack Israels LLP, One Financial Center, Boston, MA 02111

SEND CORRESPONDENCE TO

Paul S. Evans, Esq.

Specialized Health Products International, Inc.

585 West 500 South

Bountiful, Utah 84010



DIRECT TELEPHONE CALLS TO:


Paul S. Evans, (801) 298-3360

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

First Inventor:	Daniel K. Smith	
Inventor's signature:		Date 11/25/2003
Country of Citizenship:	USA	
Residence:	1473 West 1540 South Woods Cross, UT 84087	
Post Office Address:	Same as above	
Second Inventor:	Jeremy W. Snow	
Inventor's signature:		Date 11/25/2003
Country of Citizenship:	USA	
Residence:	155 North 575 East North Salt Lake, UT 84054	
Post Office Address:	Same as above	

Third Inventor:	F. Mark Ferguson	
Inventor's signature:		Date 11/25/2003
Country of Citizenship:	USA	
Residence:	1595 Treeview Drive Salt Lake City, UT 84124	